



## FOUR OUTLET MANIFOLD (1500 BAR)

The maximum working pressure for this four outlet Manifold Block is 1500 bar. The manifold blocks are assembled with self sealing quick connect couplings for fast and clean operation.

The quick connectors are fitted with plastic dust caps. Each manifold block is filled with oil and pressure tested prior to dispatch. Test certificates are supplied.

All manifolds are identified by serial numbers. They conform to the requirements of the European Pressure Equipment Directive and are CE marked.

This manifold block is ideally suited to the connection of four hydraulic bolt tensioning tools for simultaneous operation.

The manifold block is also available with 1500 bar swivels fitted to the four outlets for increased flexibility and ease of use during simultaneous bolt tensioning.

### LEGEND

- A. Four tool outlets via self sealing quick connect coupling, fitted with plastic dust caps.
- B. Inlet from pump via self sealing quick connect nipple fitted with a plastic dust cap.
- C. Plug

(See also data sheets BT-1581 and DS-612.)  
(Quick connectors are Type B, see data sheet DS-26 for details.)

HYTORC owns all content, copyrights, trademarks and patents in this document. © 2020 HYTORC. Any unauthorized use or distribution of any material from this document is strictly prohibited.

# HYTORC

**Headquarters:**  
333 Route 17 N., Mahwah, NJ 07430  
+1-201-512-9500

**Email:**  
info@hytorc.com

**Phone:**  
1-800-FOR-HYTORC

**Online:**  
hytorc.com