



This hand pump can be used with all Boltight 2500 bar tooling and equipment.

The pump has both high and low pressure pistons and is supplied complete with a 110 mm diameter pressure gauge, pressure release valve, internal pressure safety relief valve (set at 2500 bar), a 2.4 litre oil reservoir and a self sealing quick connect coupling (Type C) fitted with a red plastic dust cap.

Hand pumps should only be used with one or two tensioning tools. When simultaneous operation of several tools is being considered Boltight recommends the use of an air driven pump.

## HAND PUMP (2500 BAR)

### Specifications

#### PART NUMBER

BT-2515

#### DIMENSIONS

L: 620mm

W: 130mm

H: 170mm

#### WEIGHT

11 kg

#### OIL RESERVOIR

2.4 liters ISO 10 Hydraulic Oil

#### FINISH

Aluminum Silver

#### PRESSURE GAUGE

0 - 45000 psi (0-3000 bar)

#### MAXIMUM PRESSURE

2500 bar

#### OIL DELIVERY LOW PRESSURE PISTON

20 cc per stroke

#### OIL DELIVERY HIGH PRESSURE PISTON

0.8 cc per stroke

#### HANDLE EFFORT AT 2500 BAR

420 Newtons

The World's Most Trusted Industrial Bolting Systems

HYTORC owns all content, copyrights, trademarks and patents in this document. © 2020 HYTORC. Any unauthorized use or distribution of any material from this document is strictly prohibited.

**HYTORC**

**Headquarters:**  
333 Route 17 N., Mahwah, NJ 07430  
+1-201-512-9500

**Email:**  
info@hytorc.com

**Phone:**  
1-800-FOR-HYTORC

**Online:**  
hytorc.com