



HYTORC HYDRAULIC OIL

You choose a HYTORC Hydraulic Pump because of the HYTORC Standard of superior technology, quality, and customer support. Protect that investment with HYTORC Hydraulic Oil and regular oil changes. HYTORC Hydraulic Oil has been tested and selected to provide you with the best performance. It meets not only the ISO Standards but the HYTORC Standard as well.

CLEAN VS. DIRTY OIL



Dirty hydraulic oil performs poorly, causes overheating and premature breakdown. Clean oil is essential to keeping your pump working as efficiently as possible. Protect your pump better with clean HYTORC Hydraulic Oil to help reduce wear and prevent overheating.

CHANGE YOUR OIL



HYTORC recommends changing your oil every 6 months, or every 40 hours of runtime. Just like the oil in your car, changing your hydraulic pump oil regularly is a best practice you should be taking. If you aren't able to change the oil yourself, HYTORC can do it for you.

WHETHER YOU ARE CLOSE TO A HYTORC OFFICE
OR IN A REMOTE LOCATION, WE CAN GET YOU
THE HYTORC HYDRAULIC OIL YOU NEED.

HYTORC HYDRAULIC OIL FEATURES AND BENEFITS

FEATURES	BENEFITS
Premium Anti-Wear Additives	These additives will help reduce wear and extend pump life.
Minimal Viscosity Change	The viscosity stays consistent across a range of temperatures.
Rapid Water Separation	The effects of rust and corrosion are minimized.
Anti-Foaming Agents	This reduces air entrainment and helps with water separation.
Extended Service Life	This oil has the stability and durability to last even in the harshest conditions, lasting 5,500 hours during TOST.



THE
HYTORC
STANDARD

SUPERIOR TECHNOLOGY - SUPERIOR QUALITY - SUPERIOR CUSTOMER SUPPORT



HYTORC owns all content, copyrights, trademarks and patents in this document. © 2022 HYTORC. Any unauthorized use or distribution of any material from this document is strictly prohibited.

HYTORC

Headquarters:
333 Route 17 N., Mahwah, NJ 07430
+1-201-512-9500

Email:
info@hytorc.com

Phone:
1-800-FOR-HYTORC

Online:
hytorc.com